



The EL640.400-CB is a TFEL display for use in extreme operating conditions.

Lumineq's Thin Film Electroluminescence (TFEL) displays have the widest operating temperature range of commercially available technology.

TFEL displays are ideal for use in industrial, medical, transportation, military, public safety and other demanding applications.

Lumineq Thin Film Electroluminescent Display

Product highlights:

- Analog dimming
- 200 rows mode

General TFEL features and benefits:

- Instant ON in cold and hot temperatures
- No need for heating and cooling
- Very long lifetime
- Extremely stable brightness – measured 100,000 hours with > 85 % left of initial luminance
- TFEL display brightness, contrast, viewing angle and response time are the same across the entire operating temperature range
- Wide viewing angle > 179° with crisp and clear image
- Very fast response time, < 1 ms
- Extremely rugged and solid TFEL display structure
- Very long production life time

Ordering Information:

Product	Part number	Features
EL640.400-CB1	996-5072-00LF	Standard
EL640.400-CB1 FRA	996-5073-00LF	Aluminum frame
EL640.400-CB3 FRA	996-5078-00LF	Aluminum frame +24 VDC
EL640.400-CD4 FRA	996-5085-00LF	CB1 + ICEBrite™ + aluminum frame

Technical specifications:

Technology	Thin Film Electroluminescence
Color	TFEL-yellow
Viewing angle	179°, any viewing directions
Response time	< 1 ms
Luminance	53 cd/m ² typical areal (non-ICEBrite™) 22 cd/m ² typical areal (ICEBrite™)
Resolution	640 × 400 pixels
Pixel pitch	0.305 × 0.305 mm
Weight	400 g
Display size	225 × 147 × 23.0 mm
Active area	195 × 122 mm
Supply voltages	-CB1 and -CD4: +5 and 12 VDC -CB3: +5 and +24 VDC
Power	-CB1 and -CD4: 11 W, typical -CB3: 13 W, typical
MTBF	> 50,000 hours
Temperature	Operating: 0 to +55 °C Survival: -20 to +65 °C Storage: -40 to +85 °C
Humidity	93% RH, oper., IEC 68-2-3
Altitude	15,000 m, oper., above sea level
Shock	100 g-force, 4 ms, IEC 68-2-27
Vibration	20 to 500 Hz, 0.05 g ² /Hz random
Interface	EL standard, 1 or 2 bits/clock

Beneq is a registered trademark of Beneq Oy. ICEBrite is a trademark of Beneq Oy. Technical information in this document is subject to change without notice. Jun/2013