


**REX001602G OLED Character 16x2**



**Feature**

1. 16 characters x 2 Lines
2. Built-in controller SSD1311M1Z
3. 3V, 5V Power supply
4. 1/16 duty
5. Interface: 6800, option 8080, SPI
6. Polarizer optional

Pin No.	Symbol	Description
1	VSS	Ground Pin
2	VDD	Voltage for logic
3	NC	No Connection
4	RS	Register Select
5	R/W	Read/Write Control
6	E	Chip Enable Signal
7	DB0	Data Bus
8	DB1	Data Bus
9	DB2	Data Bus
10	DB3	Data Bus
11	DB4	Data Bus
12	DB5	Data Bus
13	DB6	Data Bus
14	DB7	Data Bus
15	NC	No Connection
16	NC	No Connection

**Mechanical Data**

Item	Standard Value	Unit
Module Dimension	84.4 x 44.0	mm
Viewing Area	58.22 x 13.52	mm
Active Area	56.22 x 11.52	mm
Dot Pitch	0.60 x 0.70	mm
Dot Size	0.57 x 0.67	mm

**Electrical Characteristics**

Item	Symbol	Condition	Standard Value			Unit
			min.	typ.	max.	
Input Voltage	VDD	---	2.8/4.8	3.0/5.0	3.3/5.3	V